

## 4GSUBHT11 HIGH VOLUME TRASH




Global Pump® portable electric submersible pumps are ideal for stationary wet pit (P type) and mobile wet pit (S type) installation.


The Model 4GSUBHT11 pump, with 4" (100 mm) NPT and an 11 hp (8 kW) motor, is ideal for medium volume, medium head applications.

### STATIONARY (SEMI PERMANENT) WET PIT INSTALLATION

DIMENSIONS (inches)

L1a	L1c	L2c	L2d	L2e	L3	L3a	L3b	L3c	L3d	L3e	L5	L5a	L5b	L5c	L5d	L6a	L6b
35.16	4.488	8.11	11.89	15.96	9.843	14.33	14.8	3.937	8.071	3.583	15.39	10.24	8.386	7.008	7.874	9.961	5.512



**SPECIFICATIONS**

Size	4" (100 mm)
Power	11 hp (8 kW)
Speed (motor)	1,754 RPM @ 60 Hz
Motor	4-pole induction continuous rated motor with squirrel cage rotor. High efficiency in compliance with "NEMA Energy Efficient Class." Stator insulation class 'H' (180°C) watertight air-filled IP68 enclosure.
Max Head	77' (23 m)
Max Flow	1,020 gpm ( 232 m <sup>3</sup> /h)
Solids Handling	4" (100 mm)
Max. temperature of the pump liquid (motor)	104°F/40°C
Max. start/stop per hour (motor)	15
Power Supply	3 phase, 60 Hz, AC Supply. Available in any voltage frequency combination (208/230/460/575 volts +/-10%)
Power Rating (motor)	11 hp @ 60 Hz
Current FLA (motor)	14.2 Amps @ 460v
Submergence	Submergence below liquid surface max. 66' (20 m)
Weight (approx. w/o cable)	P Type - 485 lbs. (220 Kg) S Type - 425 lbs. (193 Kg)

**PUMP MATERIAL**

Outer Casing	Cast Iron ASTM A48 Class 35
O-rings	Nitrile rubber
Hardware	304 Stainless steel
Shaft	431 Stainless steel
Mechanical Seals	Double with silicon carbide vs. silicon carbide faces
Impeller	Ductile iron ASTM A-395, Grade60-40-18
Ball Bearings	Rotor shaft carried in two ball bearings. Double row contact lower bearing capable of carrying high thrust and radial loads. Oversized deep groove single row upper bearing. Bearings enclosed with high temperature grease containing special anti-corrosion additive
Power Cable	Waterproof/oil proof rubber-insulated, neoprene-sheathed copper conductor flexible cable. 25' in length standard. Additional cable lengths optional.
Surface Treatment	Primer with epoxy surface treatment coated with black air dry enamel



**GLOBAL PUMP**  
10162 East Coldwater Road, Davison, MI 48423  
Tel: 810.653.4828 Fax: 810.658.0632  
**1.866.360.PUMP** [www.globalpump.com](http://www.globalpump.com)